
AR-P170FLDC-D52

Industrial Monitor with 17" Panel, Touch Screen, 4 x USB







System	
CPU	Intel Atom D525 1.8GHz
Chipset	Intel ICH8M
Memory Type	1 x 204 Pin DDR3 800MHz SO-DIMM slot
Memory Installed	2GB
LCD	
Panel Size	17" TFT-LCD
Max. Resolution	1280 x 1024
Luminance (cd/m2)	350
Backlight Lifetime	50,000hrs
Touch Screen Type	Analog Resistive
Storage	
HDD	1 x 2.5" SATA HDD Bay
CF	1 x Internal CF slot, 1 x External CF slot
I/O	
Video Interface	N/A
Ethernet	2 x 10/100Mbps RJ45 with LED
USB	4 x USB2.0
Serial Port	1 x RS-232 (DB9)
	1 x RS-422/485 (DB9, Default RS485)
Keyboard/Mouse	N/A
OSD Control	Brightness / Screen and Touch on/off / Power
	on/off At right side
Wireless LAN	Via mini-PCle optional / antenna at rear side
Expansion	N/A
Power Requiremen	nt
Power Input	DC 11~32V, with Adapter
Software	
OS Support	Windows XP, XP Embedded, Windows Embedded
	Standard 7
Mechanical & Envi	ronment
Thermal Design	Fanless
Chassis Material	Steel housing
Dimension (W x H x D)	432mm x 358mm x 67mm
Net Weight	-
IR Rating	Front panel IP65 / 6 sides IP42 with waterproof kit
Mounting	VESA75 mount
Operating Temp.	0~50°C (32~122°F)
Storage Temp.	-20~60°C (-4~140°F)
Relative Humidity	10 to 90% @ 40°C, non-condensing
Safety	CE, FCC class A



