AR-DP080

Industrial Monitor with 8" Panel, Touch Screen, 1 x VGA, 1 x COM (for Touch)









LCD	
Panel Size	8"
Max. Resolution	800 x 600
Luminance (cd/m2)	350
Backlight Lifetime	40,000 hrs
Touch Screen Type	Analog Resistive
I/O	
Video Interface	1 x VGA (Optional: DVI, RCA, S-Video)
Serial Port	1 x COM port (Optional and reserved for Touch)
Power Requiremen	t
Power Input	DC 11~32V
Power Input Mechanical & Envir	
·	ronment
Mechanical & Envir	ronment Plastic housing
Mechanical & Envir	ronment Plastic housing
Mechanical & Envir Chassis Material Dimension (W x H x D)	ronment Plastic housing 231mm x 176mm x 57mm
Mechanical & Envir Chassis Material Dimension (W x H x D) Net Weight IR Rating Mounting	Plastic housing 231mm x 176mm x 57mm 1.2kg IP65 compliant front panel Panel / VESA75 mount
Mechanical & Envir Chassis Material Dimension (W x H x D) Net Weight IR Rating	Plastic housing 231mm x 176mm x 57mm 1.2kg IP65 compliant front panel Panel / VESA75 mount 0~50°C (32–122°F)
Mechanical & Envir Chassis Material Dimension (W x H x D) Net Weight IR Rating Mounting	Plastic housing 231mm x 176mm x 57mm 1.2kg IP65 compliant front panel Panel / VESA75 mount 0~50°C (32–122°F) -20–60°C (-4~140°F)
Mechanical & Envir Chassis Material Dimension (W x H x D) Net Weight IR Rating Mounting Operating Temp.	Plastic housing 231mm x 176mm x 57mm 1.2kg IP65 compliant front panel Panel / VESA75 mount 0~50°C (32-122°F) -20~60°C (-4-140°F)







