

AES-BC27

Broadcom BCM2711 quad-core Cortex-A72 SoC IoT Edge Embedded System



Features

- Support Broadcom BCM2711 quad-core Cortex-A72 SoC @ 1.5GHz
- Onboard DDR4L 1GB / eMMC 8G (optional 2/4G RAM/16G eMMC)
- 2 x RS-232/485, 1 x isolated digital input (DI), 1 x isolated digital output (DO)
- 2 x Gigabit Ethernet
- 2 x USB 3.0 type A, 1 x CAN-FD
- 9-36V DC, wide-range power input
- Wide-range operating temperature: -20°C to 70°C



Specification

System

| | |
|------------------|--|
| Processor | Broadcom BCM2711 Quad-core Cortex-A72 1.5GHz |
| Memory | 1 /2/4 GB (model variant) |
| Storage | 8/16 GB (model variant) |
| Real time clock | Yes |
| Cellular | 1 x B-key M.2 2280/3054 (USB signaling) |
| Security | TPM 2.0 |
| Wireless LAN | WiFi 802.11 b/g/n/ac, BT 5.0 (varies with installed CM4 SOM) |
| Operating System | Raspberry Pi OS |
| LED indicators | 3 x user definable LED indicators |

Power Supply

| | |
|-------------------|----------|
| Power Requirement | 9-36 VDC |
| Power Consumption | TBD |

Environmental and Mechanical

| | |
|----------------------|---|
| Dimension | 130mm x 122mm x 57mm |
| Weight | <600g |
| Mouting/Installation | Din Rail, Wall Mount |
| Operating Temp. | -4 °F ~ 158 °F (-20 °C ~ 70 °C) |
| Storage Temp. | -40 °F ~ 176 °F (-40 °C ~ 85 °C) |
| Operating Humidity | 10% ~ 95% relative humidity, non-condensing |





Certification

| | |
|-------------|----------|
| Regulations | CE, FCC |
| Carrier | Planning |

Interface

| | |
|-----------------|---|
| Serial Port | 2 x user selectable RS-232/485 |
| CAN bus | 1 x CAN-FD, terminal block |
| DI / DO | 1 x Isolated digital input (DI); 1 x isolated digital output (DO) |
| Ethernet | 2 x GbE LAN, RJ-45 |
| USB | 2 x USB 3.2 Gen 1, type A 1 X USB 2.0 OTG |
| Display | 1 x HDMI 2.0 |
| Other Interface | 1 x SIM card slot |
| Expansion slot | M.2 B-Key 2280/3054 |

Dimensions



Ordering Information

| | |
|------------|-------------------------------------|
| AES-BC27E1 | AES-BC27, Broadcom BCM2711, 9~36VDC |
|------------|-------------------------------------|